

**Powerful and compact
colour solutions**



COPIER

Copying process:	Dry electrostatic transfer system	
Copy speed:	MP C2050: B/W / full colour: 20 copies per minute	MP C2550: B/W / full colour: 25 copies per minute
Resolution:	600 dpi	
Multiple copy:	Up to 999	
Warm-up time:	Less than 26 seconds ¹	
First output speed:	Black and white: Less than 6.5 seconds	Full colour: Less than 9.5 seconds
Zoom:	25 - 400% (in 1% steps)	
Memory:	Standard: 768 MB (upgradeable to 1 GB) + 60 GB HDD	
Paper input capacity:	Standard: 2 x 250-sheet paper trays	1 x 100-sheet bypass tray
	Maximum: 1,600 sheets	
Paper output capacity:	Maximum: 550 sheets	
Paper size:	A6 - A3	
Paper weight:	Paper tray 1: 60 - 256 g/m ²	Paper tray 2: 60 - 169 g/m ²
	Bypass tray: 52 - 256 g/m ²	Duplex tray: 60 - 105 g/m ²
Dimensions (W x D x H):	587 x 655 x 845 mm (with ARDF)	
Weight:	Less than 100 kg (with ARDF)	
Power source:	220 - 240 V, 50/60 Hz	
Power consumption:	Operation: Maximum 1,680 W ¹	

PRINTER

Print speed:	MP C2050: B/W / full colour: 20 prints per minute	MP C2550: B/W / full colour: 25 prints per minute
Printer language:	Standard: RPCS™, PCL5c, PCL6	Option: Adobe® PostScript® 3™
Resolution:	1,200 dpi	
Interface:	Standard: USB 2.0 Host USB Device Ethernet 10 base-T/100 base-TX	Option: IEEE 1284/ECP Wireless LAN (IEEE 802.11a, b, g, WPA support) Bluetooth Ethernet 1000 base-T
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX, AppleTalk	
Supported environments:	Windows® 2000/XP/Vista/Server 2003/Server 2008 Macintosh OS 8.6 or later (OS X Classic) Macintosh OS X v10.1 or later (native mode) Novell® Netware® 3.12/3.2/4.1/4.11/5.0/5.1/6/6.5 Sun® Solaris 2.6/7/8/9/10 HP-UX 10.x/11.x/11v2 SCO OpenServer 5.0.6/5.0.7/6.0 RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise IBM® AIX v4.3/5L v5.1/5L v5.2/5L v5.3 SAP® R/3® 3.x or later, mySAP ERP 2004 or later NDPS Gateway IBM iSeries AS/400® using OS/400 Host Print Transform	

SCANNER

Scan speed:	B/W: 41 images per minute (LEF, A4)	Full colour: 26 images per minute
Resolution:	Maximum 600 dpi	
Original size:	A5 - A3	
Output formats:	PDF/JPEG/TIFF/High compression PDF	
Bundled drivers:	Network, TWAIN	
Scan to e-mail:	SMTP, POP3	
Scan to e-mail destination addresses:	Maximum 500 per job	
Stored destination addresses:	Maximum 2,000	
Address book:	Via LDAP or locally on Hard Disk Drive	
Scan to folder:	SMB, FTP, NCP	
Destination:	Maximum 50 folders per job	

SOFTWARE

SmartDeviceMonitor™
Web SmartDeviceMonitor™
Web Image Monitor
DeskTopBinder™ Lite/Professional/v.5

FAX (option)

Circuit:	PSTN, PBX	
Compatibility:	ITU-T (CCITT) G3	
Modem speed:	Maximum 33.6 Kbps	
Resolution:	Standard/detail: 200 x 100/200 dpi	Maximum: 400 x 400 dpi (option)
Compression method:	MH, MR, MMR, JBIG	
Scanning speed:	36 sheets per minute	
Memory capacity:	Standard: 4 MB	Maximum: 28 MB
Memory backup:	Yes	

OTHER OPTIONS

500-sheet paper tray, 2 x 500-sheet paper trays, Caster table, Cabinet, Internal 500-sheet finisher, Punch unit, Shift tray, Inner one bin tray, Side tray, Fax unit, Fax stamp ink, Copy Data Security Unit, PictBridge, Counter interface unit type A, Key counter bracket, Remote communication gate BN1, Unicode font package for SAP, SAF memory, Data Overwrite Security Unit, HDD Encryption Unit, VM Card, Browser unit, USB2.0/SD slot, File Format Converter, 512 MB Memory unit, GlobalScan NX, Card authentication package, Professional software solutions.

¹ Warm-up time and power consumption may differ depending on the conditions and environment of the machine.

For availability of models, optional apparatus and software, please consult your local Gestetner supplier.



ISO9001: 2000 certified
ISO14001 certified

Gestetner has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2008 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.gestetner.com